

TECHNICAL DATA SHEET

LAPL IP65 / Aga-Power-Led® RGB

VERSION - 06.05.2016


STANDARD LUMINAIRE

Reference	LAPL
Protection Class	IP65
Lighting Source	Aga-Power-Led® RGB
Connector	Festoon on B'Light conductor 16mm ²
Dimensions	75 x 67mm
Standard Length	110 - 495 - 990 - 1485 - 1980mm
Length on measure	on request up to 2970mm
Nb Lighting Unit	17 LED/m
Voltage	24V
Power	54.4 W/m
Connecting Cable	One Side: 1m cable PUR 4x0.75mm ²
Grid	Anti Glare: GAP
End Caps	EFLA

APPLICATION: Upward lighting only for Walls, Facades, Columns



LAPL / Aga-Power-Led® RGB - Festoon



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising

Glass Finishing

Standard	Clear Glass
----------	-------------

ON REQUEST

Fixation	FLP Series
Recessed Box	See Data Sheet RAPI Luminaire
Connecting Plug	AMS / AF or AMS-E / AF-E (IP68)
Dimming Option	Dali, KNX <i>Ask technical departement for more information</i>

On Request: Connecting Plug

AF/AMS



AF-E/AMS-E (IP68)



LIGHTING SOURCE

Lighting Source	Aga-Power-Led® RGB
Ref	03LP22_ RGB
Power	3.2W
Voltage	24V
Beam Angle	120°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +50°C

Color Temperature & Luminous Flux / Unit

CCT	Red	Green	Blue
Luminous Flux/Unit	28 ~ 34lm	47 ~ 52lm	16 ~ 21lm

CERTIFICAT

