

## TECHNICAL DATA SHEET

### LU4ESAL IP65 / Aga-Led® Type B


VERSION - 06.01.2017

#### STANDARD LUMINAIRE

Reference	LU4ESAL
Protection Class	IP65
Lighting Source	Aga-Led® Type B
Connector	Festoon on B'Light conductor 16mm <sup>2</sup>
Dimensions	37 x 37 mm
Standard Length	515 - 1010 - 1505 - 2000mm
Length on measure	on request up to 2990mm
Nb Lighting Unit	17 LED/m
Voltage	24V
Power	With B3: 16.32W/m With B6: 20.4 W/m
Connecting Cable	Both side: 20cm standard cable 2x2.5mm <sup>2</sup>
Corner Profil	PE4
End Caps	REC4



LU4ESAL / AGA-LED® TYPE B - Festoon



#### FINISH


##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising

##### Glass Finishing

Standard	VRCE: Clear Glass
On request	VRME: Opaline

#### ON REQUEST : Without PE4 Corner / FCU Fixture Only



#### ON REQUEST

Fixation	FCU (Width:+4mm) PE4 (Width:+6mm - Ht:+7mm)
Connecting Plug	AMS / AF or AMS-E / AF-E
Dimming Option	1-10V, Dali, KNX Ask technical departement for more information

#### ON REQUEST: Connecting Plug

##### AF/AMS



##### AF-E/AMS-E (IP68)



#### LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2	
Ref	B3	B6
Power	0.96W	1.2W
Voltage	24V	24V
Beam Angle	120°	120°
CRI	80	80
Lifetime	50'000h	
Working T°	-20°C to +45°C	
Environmental protection	Modified acrylate resin	

#### Color Temperature & Luminous Flux / Unit

	2200K	2400K	2700K	3000K	4000K
Aga-Led® B3-G2	--	97 lm	137lm	137lm	137lm
Aga-Led® B6-G2	129 lm	140 lm	166 lm	166 lm	166 lm

#### CERTIFICAT



#### AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
E - mail: info@agabekov.com



AGABEKOV SA Bureau d'etudes 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
Internet: www.agabekov.com

